

BOAT TRAILER / CUSTOMER CHECKLIST BEFORE EACH USE

Congratulations on the purchase of your new boat & *Road King Trailer*. The transporting of your boat is very important. The proper care of your trailer will keep you satisfied with your purchase for years to come.

The following checklist will assist you in maintaining your trailer. *Road King Trailers*, Inc requires this list to be completed before each trip and during your annual maintenance.

	Each Use
Make sure your hitch ball properly matches the coupler size on the trailer.	\checkmark
Check lighting on trailer. Most trailers use a four wire flat connector.	\checkmark
If you have "disc" brakes you must hook up the "5" prong wire connector.	
The 5 th wire connects to the back up light on the tow vehicle to prevent brake system dam	age.
If your trailer has hydraulic brakes, maintain a full fluid level in actuator.	✓
If your trailer has hydraulic brakes, make sure the emergency brake	\checkmark
cable is not engaged (cable pulled out or lever pulled forward), otherwise brake damage ca	an occur.
Check tire pressure each time before towing. Adjust pressure to the Manufacturer's recommendation listed on tire sidewall. Note: pressure is checked on a cold tire before a t	•
recommendation listed on the sidewall. Note: pressure is checked on a cold the before a l	.mp.
Check boat to make sure it is properly tied down at transom.	\checkmark
Connect safety chain to bow eye and make sure boat is snug in winch stand bow roller.	
When connecting trailer to tow vehicle, connect safety cables/chains,	\checkmark
lighting hookup, emergency stop cable if equipped with brakes.	
Make sure coupler is properly attached with safety pin in place.	V
Place lock for added security.	
Check bearings for proper lubrication. Grease each trip.	\checkmark
Check lug nuts to make sure they are properly tightened. (90 lbs torque recommended)	\checkmark
Inspect all bolts, brackets and bunks. If loose re-tighten. If rusted beyond repair,	\checkmark
replace before using trailer. Make sure no metal parts come in contact with the hull.	
Check boat owner's manual for the proper trailering position of motor or outdrive.	~
enter cont control of manage for the proper dancing position of motor of outditte.	
Be sure to maintain safe distance between you and	\checkmark
Other vehicles as stopping distances increase when towing a trailer.	
Week your trailer often each use with a detengent seen	
Wash your trailer after each use with a detergent soap. Lubricate moving parts and use electrical grease periodically on light sockets and bolts.	v
Luoncale moving parts and use electrical grease periodically on light sockets and bolls.	